

Package: istacr (via r-universe)

October 11, 2026

Type Package
Title Obtaining Open Data from Instituto Canario De Estadistica (ISTAC) API
Version 0.3.1
Date 2026-07-09
Maintainer Elisa Jorge <ejorgon@gobiernodecanarias.org>
Description You can access to open data published in Instituto Canario De Estadistica (ISTAC) APIs at
<<https://datos.canarias.es/api/estadisticas/>>.
License GPL (>= 3)
Encoding UTF-8
LazyData true
Imports jsonlite, utils, http
Roxygen list(markdown = TRUE)
RoxygenNote 7.3.2
Depends R (>= 3.5)
Config/pak/sysreqs libssl-dev
Repository <https://ropenspain.r-universe.dev>
Date/Publication 2026-09-11 11:17:30 UTC
RemoteUrl <https://github.com/rOpenSpain/istacr>
RemoteRef HEAD
RemoteSha e375ae7402b7c6721f9e21e52890830987d80aa8

Contents

change_api_url	3
get_indicators	4
get_indicators_code	5
get_indicators_code_data	5
get_indicators_geographic_granularities	6

get_indicators_geographical_values	6
get_indicators_subjects	7
get_indicators_systems	8
get_indicators_systems_code	8
get_indicators_systems_code_instances	9
get_indicators_systems_code_instances_code	10
get_indicators_systems_code_instances_code_data	11
get_indicators_time_granularities	12
get_statisticalresources_datasets	12
get_statisticalresources_datasets_agency	13
get_statisticalresources_datasets_agency_resource	13
get_statisticalresources_datasets_agency_resource_version	14
get_statisticalresources_queries	15
get_statisticalresources_queries_agency	16
get_statisticalresources_queries_agency_resource	17
get_structuralresources_categorisations	18
get_structuralresources_categorisations_agency	19
get_structuralresources_categorisations_agency_resource	19
get_structuralresources_categorisations_agency_resource_version	20
get_structuralresources_category_schemes	21
get_structuralresources_category_schemes_agency	22
get_structuralresources_category_schemes_agency_resource	22
get_structuralresources_category_schemes_agency_resource_version	23
get_structuralresources_category_schemes_agency_resource_version_categories	24
get_structuralresources_category_schemes_agency_resource_version_categories_id	25
get_structuralresources_codelist_families	26
get_structuralresources_codelist_families_id	26
get_structuralresources_codelists	27
get_structuralresources_codelists_agency	27
get_structuralresources_codelists_agency_resource	28
get_structuralresources_codelists_agency_resource_version	29
get_structuralresources_codelists_agency_resource_version_codes	29
get_structuralresources_codelists_agency_resource_version_codes_codeid	31
get_structuralresources_codelists_agency_resource_version_recode	31
get_structuralresources_codelists_agency_resource_version_restrictions	32
get_structuralresources_concept_schemes	33
get_structuralresources_concept_schemes_agency	34
get_structuralresources_concept_schemes_agency_resource	34
get_structuralresources_concept_schemes_agency_resource_version	35
get_structuralresources_concept_schemes_agency_resource_version_concepts	36
get_structuralresources_concept_schemes_agency_resource_version_concepts_id	37
get_structuralresources_concept_types	37
get_structuralresources_content_constraints	38
get_structuralresources_content_constraints_agency	39
get_structuralresources_content_constraints_agency_resource	39
get_structuralresources_content_constraints_agency_resource_version	40
get_structuralresources_content_constraints_agency_resource_version_regions	41
get_structuralresources_data_structures	42

get_indicators

Get indicators

Description

This function returns a list of indicators published in the ISTAC-indicators database. An indicator is a measure used to know the intensity of a phenomenon in spacetime. This measure can refer to different spatial or temporal granularities.

Usage

```
get_indicators(
  q = "",
  order = "",
  limit = 25,
  offset = 0,
  fields = "",
  representation = ""
)
```

Arguments

q	(string): Metadata query on which the searches can be built using id, subjectCode or geographicValue.
order	(string): Order. Possible values are: update and id. Order criteria are ASC and DESC.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
fields	(string): Use of the answer by adding new fields. Possible values are: +metadata, +data and +observationsMetadata.
representation	(string): Allows filtering the observations by their value. Its use only makes sense when +data and/or +observationsMetadata has been included.

Examples

```
get_indicators(
  q='id IN ("AFILIACIONES", "EMPLEO_REGISTRADO_AGRICULTURA")',
  order="id ASC",
  fields="+data",
  representation="GEOGRAPHICAL[35003|35005], MEASURE[ABSOLUTE]"
)
```

get_indicators_code	<i>Get indicators code</i>
---------------------	----------------------------

Description

This function returns the metadata that describe the characteristics of a specific indicator, allowing the compression of the measured fact; also through the data request the complete data (for all spacetime) of the indicator is provided.

Usage

```
get_indicators_code(indicatorcode)
```

Arguments

indicatorcode (string): an indicator code

Examples

```
get_indicators_code("IPI_BASE_2021")  
get_indicators_code("IPI")
```

get_indicators_code_data	<i>Get indicators code data</i>
--------------------------	---------------------------------

Description

This function returns complete data (for all spacetime) of the indicator. On the other hand, metadata describing the characteristics of a specific indicator are offered through the metadata request, allowing the compression of the measured fact.

Usage

```
get_indicators_code_data(  
  indicatorcode,  
  representation = "",  
  granularity = "",  
  fields = "",  
  as_dataframe = T  
)
```

Arguments

- indicatorcode (string): an indicator code
- representation (string): Allows filtering the observations by their value.
- granularity (string): Allows to filter the observations through the granularities of the same.
- fields (string): Allows you to customize the response by excluding fields. The possible values are: -observationsMetadata.
- as_dataframe (bool): If True, this function returns a namedtuple with:
- dataframe: pandas dataframe built from API response.
 - codelists: mapping between codes and representations for each column.

Examples

```
get_indicators_code_data("IPC")
```

```
get_indicators_geographic_granularities
```

Get geographic granularities

Description

This function returns a list of geographic granularities treated in the ISTAC-indicators database. For example provincial, insular or municipal granularity.

Usage

```
get_indicators_geographic_granularities()
```

Examples

```
get_indicators_geographic_granularities()
```

```
get_indicators_geographical_values
```

Get geographical values

Description

This function returns values of a geographical granularity that in turn are part of a specific theme or system of indicators.

Usage

```
get_indicators_geographical_values(  
    geographicalgranularitycode,  
    subjectcode,  
    systemcode = ""  
)
```

Arguments

geographicalgranularitycode	(string): geographical granularity code
subjectcode	(string): subject code
systemcode	(string): system code

Examples

```
get_indicators_geographical_values(  
    "REGIONS",  
    subjectcode="051",  
    systemcode="C00067A"  
)
```

*get_indicators_subjects**Get subjects*

Description

This function returns all subjects which the ISTAC classifies its statistical operations.

Usage

```
get_indicators_subjects()
```

Examples

```
get_indicators_subjects()
```

`get_indicators_systems`*Get indicators systems*

Description

This function returns a list of indicator systems published in the ISTAC-indicators database. The indicators are simple or compound statistics, however a single indicator can rarely provide useful information about complex phenomena such as the economic situation, living conditions, schooling or others. Indicator systems are generally designed to generate more and more accurate information about the conditions of a phenomenon; and for this they are organized in dimensions or areas of analysis, under which the indicators are integrated.

Usage

```
get_indicators_systems(limit = 25, offset = 0)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.

Examples

```
get_indicators_systems()
```

`get_indicators_systems_code`*Get indicators system code*

Description

This function returns metadata of a system of indicators published in the ISTAC-indicators database. The indicators are simple or compound statistics, however a single indicator can rarely provide useful information about complex phenomena such as the economic situation, living conditions, schooling or others.

Usage

```
get_indicators_systems_code(indicatorssystemcode)
```

Arguments

indicatorssystemcode	(string): an indicator system code
----------------------	------------------------------------

Examples

```
get_indicators_systems_code("C00075H")
```

```
get_indicators_systems_code_instances
```

Get indicators system code instances

Description

This function returns instances of indicators associated with a specific indicator system. An instance of an indicator is nothing more than a spatio-temporal query of an indicator when it is incorporated into a specific indicator system.

Usage

```
get_indicators_systems_code_instances(
  indicatorsystemcode,
  q = "",
  order = "",
  limit = 25,
  offset = 0,
  fields = "",
  representation = "",
  granularity = ""
)
```

Arguments

indicatorsystemcode	(string): with an indicator system code
q	(string): Query of metadata on which the searches can be built are: id and geographicalValue.
order	(string): Order. Possible values are: update and id and order criteria are ASC and DESC.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
fields	(string): Use of the answer by adding new fields. Possible values are: +metadata, +data and +observationsMetadata.
representation	(string): Allows filtering the observations by their value. Its use only makes sense when +data and/or +observationsMetadata has been included.
granularity	(string): Allows to filter the observations through the granularities of the same. Its use only makes sense when +data and/or +observationsMetadata has been included.

Examples

```
get_indicators_systems_code_instances("C00075H")
get_indicators_systems_code_instances(
  "C00075H",
  q='id EQ "INDICADORES_MUNICIPALES"'
)
```

```
get_indicators_systems_code_instances_code
```

Get indicators system code instances code

Description

This function returns metadata of an indicator set associated with a specific indicator system. An instance of an indicator is nothing more than a spatio-temporal query of an indicator when it is incorporated into a specific indicator system.

Usage

```
get_indicators_systems_code_instances_code(
  indicatorsystemcode,
  indicatorinstancecode
)
```

Arguments

indicatorsystemcode
(string) indicator system code

indicatorinstancecode
(string) indicator instance code

Examples

```
get_indicators_systems_code_instances_code(
  "C00075H",
  "21af0477-d63b-493b-ad02-4ab181547223"
)
```

`get_indicators_systems_code_instances_code_data`*Get indicators system code instances code data*

Description

This function returns metadata of an indicator set associated with a specific indicator system. An instance of an indicator is nothing more than a spatio-temporal query of an indicator when it is incorporated into a specific indicator system.

Usage

```
get_indicators_systems_code_instances_code_data(  
  indicatorsystemcode,  
  indicatorinstancecode,  
  representation = "",  
  granularity = "",  
  fields = ""  
)
```

Arguments

<code>indicatorsystemcode</code>	(string): Indicator system code
<code>indicatorinstancecode</code>	(string): Indicator instance code
<code>representation</code>	(string): Allows filtering the observations by their value.
<code>granularity</code>	(string): Allows to filter the observations through the granularities of the same.
<code>fields</code>	(string): Allows you to customize the response by excluding fields. The possible values are: -observationsMetadata.

Examples

```
get_indicators_systems_code_instances_code_data(  
  "C00075H",  
  "21af0477-d63b-493b-ad02-4ab181547223"  
)
```

```
get_indicators_time_granularities
```

Get time granularities

Description

This function returns a list of temporary granularity treated in the ISTAC data bank-indicators ordered from highest to lowest granularity. For example annual, quarterly or monthly granularity.

Usage

```
get_indicators_time_granularities()
```

Examples

```
get_indicators_time_granularities()
```

```
get_statisticalresources_datasets
```

Get datasets

Description

This function allows consulting all existing statistical data cubes.

Usage

```
get_statisticalresources_datasets(
    lang = "es",
    limit = 25,
    offset = 0,
    orderby = "",
    query = ""
)
```

Arguments

lang	(string): Language in which you want to get the answer.
limit	(int): Results limit. By default limit=25.
offset	(int): Displacement. Result from which it is returned. By default offset=0.
orderby	(string): Order. Possible values are ID ASC or ID DESC.
query	(string): Metadata query on which the searches can be built.

Examples

```
get_statisticalresources_datasets(limit=5)
```

```
get_statisticalresources_datasets_agency
    Get datasets (agencyID)
```

Description

This function allows to consult all the data sets maintained by a certain organization.

Usage

```
get_statisticalresources_datasets_agency(
    agencyid,
    lang = "es",
    limit = 25,
    offset = 0,
    orderby = "",
    query = ""
)
```

Arguments

agencyid	(string): Identifier of the maintainer organization of the resource. A possible value is ISTAC.
lang	(string): Language in which you want to get the answer.
limit	(int): Results limit. By default limit=25.
offset	(int): Displacement. Result from which it is returned. By default offset=0.
orderby	(string): Order. Possible values are ID ASC or ID DESC.
query	(string): Metadata query on which the searches can be built.

Examples

```
get_statisticalresources_datasets_agency(agencyid="ISTAC")
```

```
get_statisticalresources_datasets_agency_resource
    Get datasets (agencyID / resourceID)
```

Description

This function allows to obtain all the versions of a statistical cube with a certain identifier and that also maintains a certain organization.

Usage

```

get_statisticalresources_datasets_agency_resource(
    agencyid,
    resourceid,
    lang = "es",
    limit = 25,
    offset = 0,
    orderby = "",
    query = ""
)

```

Arguments

agencyid	(string): Identifier of the maintainer organization of the resource. A possible value is ISTAC.
resourceid	(string): Resource identifier. A possible value is C00010A_000002.
lang	(string): Language in which you want to get the answer.
limit	(int): Results limit. By default limit=25.
offset	(int): Displacement. Result from which it is returned. By default offset=0.
orderby	(string): Order. Possible values are ID ASC or ID DESC.
query	(string): Metadata query on which the searches can be built.

Examples

```

get_statisticalresources_datasets_agency_resource(
    agencyid="ISTAC",
    resourceid="C00010A_000002"
)

```

```

get_statisticalresources_datasets_agency_resource_version
    Get datasets (agencyID / resourceID / version)

```

Description

This function allows to obtain a certain version of a statistical cube with a certain identifier and that also maintains a certain organization.

Usage

```

get_statisticalresources_datasets_agency_resource_version(
    agencyid,
    resourceid,
    version,
    dim = "",

```

```

    representation = "",
    granularity = "",
    fields = "",
    lang = "es",
    as_dataframe = T
  )

```

Arguments

agencyid	(string): Identifier of the maintainer organization of the resource. A possible value is ISTAC.
resourceid	(string): Resource identifier. A possible value is C00010A_000002.
version	(string): Resource version. A possible value is 001.000.
dim	(string): Allows filtering the data obtained in the response. An example is TIME_PERIOD:2009 2010.
representation	(string): Specifies the representation format of the returned data. Leave empty to use the API default.
granularity	(string): Specifies the desired level of aggregation or granularity for the returned data. Leave empty to use the API default.
fields	(string): Allows you to customize the response by excluding fields from it. The possible values are -metadata and -data.
lang	(string): Language in which you want to get the answer.
as_dataframe	(bool): If TRUE, this function returns a list with: • dataframe: data.frame built from the API response. • codelists: mapping between codes and representations for each column.

Examples

```

get_statisticalresources_datasets_agency_resource_version(
  agencyid = "ISTAC",
  resourceid = "E68025A_000007",
  version = "~latest",
  representation = "TIME_PERIOD[~last=1]:MEDIDAS[CASO_ACTIV]:TERRITORIO[ES70]")$dataframe

```

```

get_statisticalresources_queries
  Get queries

```

Description

This function allows consulting all existing statistical queries.

Usage

```
get_statisticalresources_queries(  
    lang = "es",  
    limit = 25,  
    offset = 0,  
    orderby = "",  
    query = ""  
)
```

Arguments

lang	(string): Language in which you want to get the answer.
limit	(int): Results limit. By default limit=25.
offset	(int): Displacement. Result from which it is returned. By default offset=0.
orderby	(string): Order. Possible values are ID ASC or ID DESC,
query	(string): Metadata query on which the searches can be built.

Examples

```
get_statisticalresources_queries(limit=5)
```

```
get_statisticalresources_queries_agency  
    Get queries (agencyID)
```

Description

This function allows to consult all the queries maintained by a certain organization.

Usage

```
get_statisticalresources_queries_agency(  
    agencyid,  
    lang = "es",  
    limit = 25,  
    offset = 0,  
    orderby = "",  
    query = ""  
)
```

Arguments

agencyid	(string): Identifier of the maintainer organization of the resource. A possible value is ISTAC.
lang	(string): Language in which you want to get the answer.
limit	(int): Results limit. By default limit=25.
offset	(int): Displacement. Result from which it is returned. By default offset=0.
orderby	(string): Order. Possible values are ID ASC or ID DESC,
query	(string): Metadata query on which the searches can be built.

Examples

```
get_statisticalresources_queries_agency(agencyid="ISTAC", limit=5)
```

```
get_statisticalresources_queries_agency_resource
    Get queries (agencyID / resourceID)
```

Description

This function allows to obtain final data of a statistical query with a certain identifier and that also maintains a certain organization.

Usage

```
get_statisticalresources_queries_agency_resource(
    agencyid,
    resourceid,
    fields = "",
    lang = "es",
    as_dataframe = T
)
```

Arguments

agencyid	(string): Identifier of the maintainer organization of the resource. A possible value is ISTAC.
resourceid	(string): Resource identifier. A possible value is C00005A_000004.
fields	(string): Allows you to customize the response by excluding fields from it. The possible values are -metadata and -data.
lang	(string): Language in which you want to get the answer.
as_dataframe	(bool): If True, this function returns a namedtuple with: - dataframe: pandas dataframe built from API response. - codelists: mapping between codes and representations for each column.

Examples

```
get_statisticalresources_queries_agency_resource(  
    agencyid="ISTAC",  
    resourceid="C00005A_000004"  
)
```

```
get_structuralresources_categorisations  
Get categorisations
```

Description

This function returns the content from /v1.0/categorisations

Usage

```
get_structuralresources_categorisations(  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset=0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_categorisations()  
get_structuralresources_categorisations(  
    query="ID EQ 2090",  
    orderby="ID ASC"  
)
```

get_structuralresources_categorisations_agency
Get categorisations agency

Description

This function returns the content from `/v1.0/categorisations/{agencyID}`

Usage

```
get_structuralresources_categorisations_agency(  
    agencyid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset=0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_categorisations_agency("ISTAC")
```

get_structuralresources_categorisations_agency_resource
Get categorisations agency resource

Description

This function returns the content from `/v1.0/categorisations/{agencyID}/{resourceID}`

Usage

```
get_structuralresources_categorisations_agency_resource(  
    agencyid,  
    resourceid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset=0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_categorisations_agency_resource("ISTAC", "cat2")
```

```
get_structuralresources_categorisations_agency_resource_version
```

Get categorisations agency resource version

Description

This function returns the content from `/v1.0/categorisations/{agencyID}/{resourceID}/{version}`

Usage

```
get_structuralresources_categorisations_agency_resource_version(  
    agencyid,  
    resourceid,  
    version  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
version	(string): Specific version of the resource.

Examples

```
get_structuralresources_categorisations_agency_resource_version(  
    "ISTAC",  
    "cat2",  
    "01.000"  
)
```

```
get_structuralresources_category_schemes  
    Get category schemes
```

Description

This function returns the content from /v1.0/categoryschemes

Usage

```
get_structuralresources_category_schemes(  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_category_schemes()  
get_structuralresources_category_schemes(  
    query="ID EQ 2090",  
    orderby="ID ASC"  
)
```

```
get_structuralresources_category_schemes_agency
```

Get category schemes agency

Description

This function returns the content from `/v1.0/categoryschemes/{agencyID}`

Usage

```
get_structuralresources_category_schemes_agency(  
    agencyid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_category_schemes_agency(  
    "ISTAC",  
    query="ID EQ 2090",  
    orderby="ID ASC"  
)
```

```
get_structuralresources_category_schemes_agency_resource
```

Get category schemes agency resource

Description

This function returns the content from `/v1.0/categoryschemes/{agencyID}/{resourceID}`

Usage

```
get_structuralresources_category_schemes_agency_resource(  
    agencyid,  
    resourceid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_category_schemes_agency_resource(  
    "ISTAC",  
    "TEMAS_CANARIAS"  
)
```

get_structuralresources_category_schemes_agency_resource_version
Get category schemes agency resource version

Description

This function returns the content from `/v1.0/categoryschemes/{agencyID}/{resourceID}/{version}`

Usage

```
get_structuralresources_category_schemes_agency_resource_version(  
    agencyid,  
    resourceid,  
    version  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
version	(string): Specific version of the resource.

Examples

```
get_structuralresources_category_schemes_agency_resource_version(  
    "ISTAC",  
    "TEMAS_CANARIAS",  
    "01.000"  
)
```

```
get_structuralresources_category_schemes_agency_resource_version_categories  
    Get category schemes agency resource version categories
```

Description

This function returns the content from `/v1.0/categorieschemes/{agencyID}/{resourceID}/{version}/categories`

Usage

```
get_structuralresources_category_schemes_agency_resource_version_categories(  
    agencyid,  
    resourceid,  
    version,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
version	(string): Specific version of the resource.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_category_schemes_agency_resource_version_categories(  
    "ISTAC",  
    "TEMAS_CANARIAS",  
    "01.000"  
)
```

get_structuralresources_category_schemes_agency_resource_version_categories_id
Get category schemes agency resource version categories (id)

Description

This function returns the content from /v1.0/categorieschemes/{agencyID}/{resourceID}/{version}/categories/{categoryID}

Usage

```
get_structuralresources_category_schemes_agency_resource_version_categories_id(  
    agencyid,  
    resourceid,  
    version,  
    categoryid  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
version	(string): Specific version of the resource.
categoryid	(string): category identifier.

Examples

```
get_structuralresources_category_schemes_agency_resource_version_categories_id(  
    "ISTAC",  
    "TEMAS_CANARIAS",  
    "01.000",  
    "060"  
)  
get_structuralresources_category_schemes_agency_resource_version_categories_id(  
    "ISTAC",  
    "TEMAS_CANARIAS",  
    "01.000",  
    "060.060_010.060_010_010"  
)
```

```
get_structuralresources_codelist_families
```

Get codelist families

Description

This function returns the list of families of classifications

Usage

```
get_structuralresources_codelist_families(
    limit = 25,
    offset = 0,
    orderby = "",
    query = ""
)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
orderby	(string): Field by which to sort the results.
query	(string): Query to filter the results.

Examples

```
get_structuralresources_codelist_families()
```

```
get_structuralresources_codelist_families_id
```

Get codelist families

Description

This function allows to obtain a family of classifications in particular.

Usage

```
get_structuralresources_codelist_families_id(id)
```

Arguments

id	(string): codelist family identificator
----	---

Examples

```
get_structuralresources_codelist_families_id('CODELIST_ID')
```

get_structuralresources_codelists
Get codelists

Description

This function allows to obtain the list of classifications.

Usage

```
get_structuralresources_codelists(  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_codelists()
```

get_structuralresources_codelists_agency
Get codelists agency

Description

This function allows obtaining the list of all the classifications maintained by a certain organization.

Usage

```
get_structuralresources_codelists_agency(  
    agencyid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Agency identificator.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_codelists_agency("ISTAC")
get_structuralresources_codelists_agency("ESTAT")
```

```
get_structuralresources_codelists_agency_resource
    Get codelists agency resource
```

Description

This function allows to obtain all the versions of a classification with a certain identifier and that is also kept by a certain organization.

Usage

```
get_structuralresources_codelists_agency_resource(
    agencyid,
    resourceid,
    limit = 25,
    offset = 0,
    query = "",
    orderby = ""
)
```

Arguments

agencyid	(string): Agency identificator.
resourceid	(string): Resource identificator.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_codelists_agency_resource("ISTAC", "CL_AREA_ES")
```

```
get_structuralresources_codelists_agency_resource_version
```

Get codelists agency resource version

Description

This function allows you to consult a particular version of a classification.

Usage

```
get_structuralresources_codelists_agency_resource_version(  
  agencyid,  
  resourceid,  
  version  
)
```

Arguments

agencyid	(string): Agency identificator.
resourceid	(string): Resource identificator.
version	(string): Specific resource version.

Examples

```
get_structuralresources_codelists_agency_resource_version(  
  "ISTAC",  
  "CL_AREA_ES",  
  "01.000"  
)
```

```
get_structuralresources_codelists_agency_resource_version_codes
```

Get codelists agency resource version codes

Description

This function allows to consult the codes of a version of a classification. Note that if wildcards are used as ~all or one of the limit, offset, query or orderBy parameters, the list will be automatically paginated.

Usage

```

get_structuralresources_codelists_agency_resource_version_codes(
    agencyid,
    resourceid,
    version,
    limit = 1000,
    offset = 0,
    query = "",
    orderby = "",
    openness = "",
    order = "",
    fields = "",
    lang = "es",
    as_dataframe = T
)

```

Arguments

agencyid	(string): Agency identificator.
resourceid	(string): Resource identificator.
version	(string): Specific resource version.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results. orderby (string): Field by which to sort the results.
orderby	(string): Order established for data.
openness	(string): Opening established for viewing.
order	(string): Order established for visualization.
fields	(string): Additional fields that you want to show in the answer.
lang	(string): Language in which you want to get the answer.
as_dataframe	(bool): If True, this function returns a pandas dataframe built from API response.

Examples

```

get_structuralresources_codelists_agency_resource_version_codes(
    "ISTAC",
    "CL_AREA_ES",
    "01.000"
)

```

```
get_structuralresources_codelists_agency_resource_version_codes_codeid
```

Get codelists agency resource version codes (codeID)

Description

This function allows to consult a specific code of a version of a classification.

Usage

```
get_structuralresources_codelists_agency_resource_version_codes_codeid(  
  agencyid,  
  resourceid,  
  version,  
  codeid  
)
```

Arguments

agencyid	(string): Agency identificator.
resourceid	(string): Resource identificator.
version	(string): Specific resource version.
codeid	(string): Code identificator.

Examples

```
get_structuralresources_codelists_agency_resource_version_codes_codeid(  
  "ISTAC", "CL_AREA_ES", "01.000", "ES706A01")
```

```
get_structuralresources_codelists_agency_resource_version_recode
```

Get codelists agency resource version recode

Description

This function allows to see changes between two classifications.

Usage

```
get_structuralresources_codelists_agency_resource_version_recode(  
  agencyid,  
  resourceid,  
  version,  
  referenceagencyid,  
  referenceresourceid,  
  referenceversion  
)
```

Arguments

agencyid (string): Agency identifier.
 resourceid (string): Resource identifier.
 version (string): Specific resource version.
 referenceagencyid (string): Reference agency identifier.
 referenceresourceid (string): Reference resource identifier.
 referenceversion (string): Reference specific resource version.

Examples

```

get_structuralresources_codelists_agency_resource_version_recode(
  "ISTAC",
  "CL_AREA_ES",
  "01.001",
  "ISTAC",
  "CL_AREA_ES_RELATIVA",
  "~latest"
)

```

get_structuralresources_codelists_agency_resource_version_restrictions
Get codelists agency resource version restrictions

Description

This function allows you to consult any restrictions for a specific code of a version of a classification.

Usage

```

get_structuralresources_codelists_agency_resource_version_restrictions(
  agencyid,
  resourceid,
  version
)

```

Arguments

agencyid (string): Agency identifier.
 resourceid (string): Resource identifier.
 version (string): Specific resource version.

Examples

```
get_structuralresources_codelists_agency_resource_version_restrictions(  
    "ISTAC",  
    "CL_AREA_ES",  
    "~latest"  
)
```

```
get_structuralresources_concept_schemes  
    Get concept schemes
```

Description

This function returns the content from `/v1.0/conceptschemes`

Usage

```
get_structuralresources_concept_schemes(  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_concept_schemes()  
get_structuralresources_concept_schemes(  
    query="ID EQ 2090",  
    orderby="ID ASC"  
)
```

```
get_structuralresources_concept_schemes_agency
```

Get concept schemes agency

Description

This function returns the content from `/v1.0/conceptschemes/{agencyID}`

Usage

```
get_structuralresources_concept_schemes_agency(  
    agencyid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_concept_schemes_agency("ISTAC")  
get_structuralresources_concept_schemes_agency(  
    "ESTAT",  
    query="ID EQ 2090",  
    orderby="ID ASC"  
)
```

```
get_structuralresources_concept_schemes_agency_resource
```

Get concept schemes agency resource

Description

This function returns the content from `/v1.0/conceptschemes/{agencyID}/{resourceID}`

Usage

```

get_structuralresources_concept_schemes_agency_resource(
    agencyid,
    resourceid,
    limit = 25,
    offset = 0,
    query = "",
    orderby = ""
)

```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```

get_structuralresources_concept_schemes_agency_resource(
    agencyid="ISTAC",
    resourceid="CSM_C00010A_SIE"
)

```

```

get_structuralresources_concept_schemes_agency_resource_version
    Get concept schemes agency resource version

```

Description

This function returns the content from `/v1.0/conceptschemes/{agencyID}/{resourceID}/{version}`

Usage

```

get_structuralresources_concept_schemes_agency_resource_version(
    agencyid,
    resourceid,
    version
)

```

Arguments

agencyid	(string) Identifier of the agency that publishes.
resourceid	(string) Resource identifier.
version	(string) Specific version of the resource.

Examples

```
get_structuralresources_concept_schemes_agency_resource_version(
  agencyid="ISTAC",
  resourceid="CSM_C00010A_SIE",
  version="01.000"
)
```

```
get_structuralresources_concept_schemes_agency_resource_version_concepts
```

Get concept schemes agency resource version concepts

Description

This function returns the content from `/v1.0/concept_schemes/{agencyID}/{resourceID}/{version}/concepts`

Usage

```
get_structuralresources_concept_schemes_agency_resource_version_concepts(
  agencyid,
  resourceid,
  version,
  limit = 25,
  offset = 0,
  query = "",
  orderby = "",
  fields = ""
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
version	(string): Specific version of the resource.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.
fields	(string): Additional fields that you want to show in the answer.

Examples

```
get_structuralresources_concept_schemes_agency_resource_version_concepts(
  agencyid="ISTAC",
  resourceid="CSM_C00010A_SIE",
  version="01.000"
)
```

get_structuralresources_concept_schemes_agency_resource_version_concepts_id
Get concept schemes agency resource version concepts (id)

Description

This function returns the content from /v1.0/conceptschemes/{agencyID}/{resourceID}/{version}/concepts/{conceptID}

Usage

```
get_structuralresources_concept_schemes_agency_resource_version_concepts_id(  
    agencyid,  
    resourceid,  
    version,  
    conceptid  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
version	(string): Specific version of the resource.
conceptid	(string): Concept identifier.

Examples

```
get_structuralresources_concept_schemes_agency_resource_version_concepts_id(  
    agencyid="ISTAC",  
    resourceid="CSM_C00010A_SIE",  
    version="01.000",  
    conceptid="ELECTORES"  
)
```

get_structuralresources_concept_types
Get concept types

Description

This function returns the content from /v1.0/conceptTypes

Usage

```
get_structuralresources_concept_types()
```

Examples

```
get_structuralresources_concept_types()
```

```
get_structuralresources_content_constraints
```

Get content constraints

Description

This function returns the content from /v1.0/contentConstraints

Usage

```
get_structuralresources_content_constraints(  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_content_constraints()  
get_structuralresources_content_constraints(  
    query="ID EQ 2090",  
    orderby="ID ASC"  
)
```

get_structuralresources_content_constraints_agency
Get content constraints agency

Description

This function returns the content from /v1.0/contentConstraints/{agencyID}

Usage

```
get_structuralresources_content_constraints_agency(  
    agencyid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_content_constraints_agency("ISTAC")
```

get_structuralresources_content_constraints_agency_resource
Get content constraints agency resource

Description

This function returns the content from /v1.0/contentConstraints/{agencyID}/{resourceID}

Usage

```
get_structuralresources_content_constraints_agency_resource(
    agencyid,
    resourceid,
    limit = 25,
    offset = 0,
    query = "",
    orderby = ""
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_content_constraints_agency_resource(
    "ISTAC",
    "CSM_C00010A_SIE"
)
```

```
get_structuralresources_content_constraints_agency_resource_version
```

Get content constraints agency resource version

Description

This function returns the content from `/v1.0/contentConstraints/{agencyID}/{resourceID}/{version}`

Usage

```
get_structuralresources_content_constraints_agency_resource_version(
    agencyid,
    resourceid,
    version
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
version	(string): Specific version of the resource.

Examples

```
get_structuralresources_content_constraints_agency_resource_version(  
    "ISTAC",  
    "CSM_C00010A_SIE",  
    "01.000"  
)
```

get_structuralresources_content_constraints_agency_resource_version_regions
Get content constraints agency resource version regions

Description

This function returns the content from /v1.0/contentConstraints/{agencyID}/{resourceID}/{version}/regions/{r

Usage

```
get_structuralresources_content_constraints_agency_resource_version_regions(  
    regioncode,  
    agencyid,  
    resourceid,  
    version  
)
```

Arguments

regioncode	(string) Region code.
agencyid	(string) Identifier of the agency that publishes.
resourceid	(string) Resource identifier.
version	(string) Specific version of the resource.

Examples

```
get_structuralresources_content_constraints_agency_resource_version_regions(  
    "0001",  
    "ISTAC",  
    "CSM_C00010A_SIE",  
    "01.000"  
)
```

get_structuralresources_data_structures
Get data structures

Description

This function returns the content from /v1.0/datastructures

Usage

```
get_structuralresources_data_structures(  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_data_structures()  
get_structuralresources_data_structures(  
    query="ID EQ 2090",  
    orderby="ID ASC"  
)
```

get_structuralresources_data_structures_agency
Get data structures agency

Description

This function returns the content from /v1.0/datastructures/{agencyID}

Usage

```
get_structuralresources_data_structures_agency(  
    agencyid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_data_structures_agency("ISTAC")
```

```
get_structuralresources_data_structures_agency_resource
```

Get data structures agency resource

Description

This function returns the content from `/v1.0/datastructures/{agencyID}/{resourceID}`

Usage

```
get_structuralresources_data_structures_agency_resource(  
    agencyid,  
    resourceid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_data_structures_agency_resource(
  "ISTAC",
  "DSD_C00010A_00001"
)
```

```
get_structuralresources_data_structures_agency_resource_version
  Get data structures agency resource version
```

Description

This function returns the content from `/v1.0/datastructures/{agencyID}/{resourceID}/{version}`

Usage

```
get_structuralresources_data_structures_agency_resource_version(
  agencyid,
  resourceid,
  version
)
```

Arguments

agencyid	(string): Identifier of the agency that publishes.
resourceid	(string): Resource identifier.
version	(string): Specific version of the resource.

Examples

```
get_structuralresources_data_structures_agency_resource_version(
  "ISTAC",
  "DSD_C00010A_00001",
  "01.001"
)
```

```
get_structuralresources_geoinfo
    Get geoinfo
```

Description

This function returns data from /v1.0/variables/{variableID}/variableelements/{resourceID}/geoinfo

Usage

```
get_structuralresources_geoinfo(  
    variableid,  
    resourceid,  
    fields = "",  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

variableid	(string): Variable identificator.
resourceid	(string): Resource identificator.
fields	(string): Additional fields that you want to show in the answer.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_geoinfo("VR_TERRITORIO", "MUN_ICOD_VINOS")
```

```
get_structuralresources_variable_families
    Get variable families
```

Description

This function returns data from /v1.0/variablefamilies

Usage

```
get_structuralresources_variable_families(
    limit = 25,
    offset = 0,
    query = "",
    orderby = ""
)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_variable_families()
```

```
get_structuralresources_variable_families_id
    Get variable families (id)
```

Description

This function returns data from /v1.0/variablefamilies/{id}

Usage

```
get_structuralresources_variable_families_id(id)
```

Arguments

id	(string): Variable family identifier.
----	---------------------------------------

Examples

```
get_structuralresources_variable_families_id("VRF_DEMOGRAFICAS")
```

```
get_structuralresources_variable_families_id_variables
```

Get variable families (id) variables

Description

This function returns data from /v1.0/variablefamilies/{id}/variables

Usage

```
get_structuralresources_variable_families_id_variables(  
    id,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

id	(string): Variable family identificator.
limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_variable_families_id_variables("VRF_DEMOGRAFICAS")
```

```
get_structuralresources_variableelements
```

Get variableelements

Description

This function returns data from /v1.0/variables/{variableID}/variableelements

Usage

```
get_structuralresources_variableelements(  
    variableid,  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

variableid	(string) Variable identifier.
limit	(int) Results limit. By default limit = 25.
offset	(int) Displacement. Result from which it is returned. By default offset = 0.
query	(string) Query to filter the results.
orderby	(string) Field by which to sort the results.

Examples

```
get_structuralresources_variableelements("VR_SEX0")
```

get_structuralresources_variableelements_resource
<i>Get variableelements resource</i>

Description

This function returns data from /v1.0/variables/{variableID}/variableelements/{resourceID}

Usage

```
get_structuralresources_variableelements_resource(variableid, resourceid)
```

Arguments

variableid	(string): Resource identifier.
resourceid	(string): Variable identifier.

Examples

```
get_structuralresources_variableelements_resource("VR_SEX0", "FEMALE")
```

get_structuralresources_variables
<i>Get variables</i>

Description

This function returns data from /v1.0/variables

Usage

```
get_structuralresources_variables(  
    limit = 25,  
    offset = 0,  
    query = "",  
    orderby = ""  
)
```

Arguments

limit	(int): Results limit. By default limit = 25.
offset	(int): Displacement. Result from which it is returned. By default offset = 0.
query	(string): Query to filter the results.
orderby	(string): Field by which to sort the results.

Examples

```
get_structuralresources_variables()
```

```
get_structuralresources_variables_id  
    Get variables (id)
```

Description

This function returns data from /v1.0/variables/{id}

Usage

```
get_structuralresources_variables_id(id)
```

Arguments

id	(string): Variable identifier.
----	--------------------------------

Examples

```
get_structuralresources_variables_id("VR_SEX0")
```

Index

[change_api_url](#), [3](#)
[get_indicators](#), [4](#)
[get_indicators_code](#), [5](#)
[get_indicators_code_data](#), [5](#)
[get_indicators_geographic_granularities](#),
[6](#)
[get_indicators_geographical_values](#), [6](#)
[get_indicators_subjects](#), [7](#)
[get_indicators_systems](#), [8](#)
[get_indicators_systems_code](#), [8](#)
[get_indicators_systems_code_instances](#),
[9](#)
[get_indicators_systems_code_instances_code](#),
[10](#)
[get_indicators_systems_code_instances_code_data](#),
[11](#)
[get_indicators_time_granularities](#), [12](#)
[get_statisticalresources_datasets](#), [12](#)
[get_statisticalresources_datasets_agency](#),
[13](#)
[get_statisticalresources_datasets_agency_resource](#),
[13](#)
[get_statisticalresources_datasets_agency_resource_version](#),
[14](#)
[get_statisticalresources_queries](#), [15](#)
[get_statisticalresources_queries_agency](#),
[16](#)
[get_statisticalresources_queries_agency_resource](#),
[17](#)
[get_structuralresources_categorisations](#),
[18](#)
[get_structuralresources_categorisations_agency](#),
[19](#)
[get_structuralresources_categorisations_agency_resource](#),
[19](#)
[get_structuralresources_categorisations_agency_resource_version](#),
[20](#)
[get_structuralresources_category_schemes](#),
[21](#)
[get_structuralresources_category_schemes_agency](#),
[22](#)
[get_structuralresources_category_schemes_agency_resource](#),
[22](#)
[get_structuralresources_category_schemes_agency_resource_v](#),
[23](#)
[get_structuralresources_category_schemes_agency_resource_v](#),
[24](#)
[get_structuralresources_category_schemes_agency_resource_v](#),
[25](#)
[get_structuralresources_codelist_families](#),
[26](#)
[get_structuralresources_codelist_families_id](#),
[26](#)
[get_structuralresources_codelists](#), [27](#)
[get_structuralresources_codelists_agency](#),
[27](#)
[get_structuralresources_codelists_agency_resource](#),
[28](#)
[get_structuralresources_codelists_agency_resource_version](#),
[29](#)
[get_structuralresources_codelists_agency_resource_version](#),
[29](#)
[get_structuralresources_codelists_agency_resource_version](#),
[31](#)
[get_structuralresources_codelists_agency_resource_version](#),
[31](#)
[get_structuralresources_codelists_agency_resource_version](#),
[32](#)
[get_structuralresources_concept_schemes](#),
[33](#)
[get_structuralresources_concept_schemes_agency](#),
[34](#)
[get_structuralresources_concept_schemes_agency_resource](#),
[34](#)
[get_structuralresources_concept_schemes_agency_resource_v](#),
[35](#)
[get_structuralresources_concept_schemes_agency_resource_v](#),
[36](#)

`get_structuralresources_concept_schemes_agency_resource_version_concepts_id,`
37
`get_structuralresources_concept_types,`
37
`get_structuralresources_content_constraints,`
38
`get_structuralresources_content_constraints_agency,`
39
`get_structuralresources_content_constraints_agency_resource,`
39
`get_structuralresources_content_constraints_agency_resource_version,`
40
`get_structuralresources_content_constraints_agency_resource_version_regions,`
41
`get_structuralresources_data_structures,`
42
`get_structuralresources_data_structures_agency,`
42
`get_structuralresources_data_structures_agency_resource,`
43
`get_structuralresources_data_structures_agency_resource_version,`
44
`get_structuralresources_geoinfo,` 45
`get_structuralresources_variable_families,`
45
`get_structuralresources_variable_families_id,`
46
`get_structuralresources_variable_families_id_variables,`
47
`get_structuralresources_variableelements,`
47
`get_structuralresources_variableelements_resource,`
48
`get_structuralresources_variables,` 48
`get_structuralresources_variables_id,`
49